

Vietnam Polystyrene Co., Ltd Polystyrene

General Purpose

Committed to Quality and Technology

Website: www.vietnampolystyrene.com

The only Vietnam PS factory located in Vung Tau.

越南唯一PS製造工廠

VNPS GPPS-550N are General Purposes Polystyrene having excellent clarity and gloss. They are available in Non-Blue tint and have good dimensional stability at high temperature.

DESCRIPTION:

Heat resistance, Extreme Low Volatility & Injection Grade (below 750 ppm). GPPS-550N

SPECIFICATIONS:									
GRADE	TENSILE PROPERTIES ASTM D-638		IMPACT PROPERTIES ASTM D-256		FLEXURAL PROPERTY ASTM D-790	THERMAL PROPERTY		OTHER PROPERTIES	
						ASTM D-648	ASTM D-1525		
	Tensile	Elongation	Izod Impact Strength	Gardner Falling Dart		HDT	Vicat Softening Temp.	Melt Flow Index	Specific Gravity
	Kgs/Cm ²	%	Kgf-Cm/Cm	Cm-Kg	Kgs/Cm ²	0C	oC	Gm/10mins.	ı
GPPS- 550N	440	2	1.6	-	750	92	98	5 ± 1	1.04

Remarks: The data intended as general guide only and do not represent results that may be obtained elsewhere.

CHARACTERISTICS:

Non-Blue Tint, Excellent Clarity, Good Flow and Low Volatility (below 750 ppm).

APPLICATIONS:

GPPS-550N:

House ware, containers, toys, Ball point pen, Drinking cups and thin wall applications.

VIETNAM POLYSTYRENE CO., LTD

Dong Xuyen Industrial Zone

Rach Dua Ward, Vung Tau City Vietnam Tel: +84-64 3615 771~4 Fax: +84-64 3615 384

Email: sales@vietnampolystyrene.com Web: www.vietnampolystyrene.com